

Product data sheet

GEZE ActiveStop integrated

Draw-in damper on both sides for single-action doors without fire protection requirements



Product features

Door opening angle with variable adjustment, ranging from 80°-140°.
Can be used for right and left hand doors without conversion
Controlled opening and closing of doors up to max. 45 kg leaf weight
Gentle stopping and silent closing, and doors are kept open with ease
Slamming doors, jammed fingers, damage to walls and furniture are virtually impossible.
Safe hold of the door when open, no door stopper required
When installed, the back check and closing damping settings can be made via a valve
Integrated safety valve offers protection against overload

Application Areas

Right and left timber single-action doors indoors
Room doors with high access convenience
Single-action doors up to 1100 mm leaf width
Integrated installation in the door leaf
Barrier-free access in accordance with DIN 18040

Product Data Table

Productname	GEZE ActiveStop integrated
Installation depth	28 mm
Height	64 mm
Leaf weight (max.)	45 kg
Leaf width (max.)	1100 mm
Leaf material	Wood
Leaf thickness from	38 mm
Same version for DIN left and DIN right	true
Rebate space	approx. 6 mm clearance in handle area
Draw-in damper in direction of closing movement from	25 °
Free swing area	25 ° - 60 °
Draw-in damper in direction of opening movement from	60 °
Door opening angle	80 ° - 140 °
Secured final position	Safe holding of the door in the open position, no door stop needed
Safety valve againts overload	Yes
Latch blockers	Supplied by GEZE

Accessory

Product name
Milling edge cover
Milling fixture
Fixing plates for guide rails