

Draft specification



MANULIFT 6380HA - 110,0 cm
Manufacturer: Granberg

Article Info

MANULIFT 6380H is a manually adjustable worktop unit. Under the worktop, space is left for the knees and legs. Installations under the worktop, (brackets, water, sewers), can be concealed by telescopic cover panels which gives the kitchen a neat look. The height is adjustable by 300 mm at 25 mm intervals.
A built-in gas spring facilitates the adjustment. The lift is prepared in the factory to facilitate easy installation.

Art.no	Description	EAN
6380HA-110	MANULIFT 6380HA - 110,0 cm	7340193103717

Specifications

Installation

Wall-mounted

Front height

103 mm

Plumbing connections

Connection is made with flexible hoses

Height adjustment

Manually adjustable by 300 mm in intervals of 25 mm

(700-1000 mm excl. top board)

A built-in gas spring facilitates height adjustment:

Pull out the locking pin, adjust the height with the help of the gas spring.

Lock the position with the locking pin.

Max load

100 kg

Frame depth

560-590 mm from wall

Dimensions cover plates

2 pcs, width = width of the lift -10 mm, height 438 mm, thickness 12-20 mm

Width worktop

Width = width of the lift

Depth worktop

565-630 mm (15 mm shallower than worktops on fixed cabinets)

Space to wall / adjoining cabinet

5 mm

Space to wall (for tiles)

15 mm

Tiling

From 700 mm above floor (alternatively all the way down to the floor)

Delivery modules

Ready-mounted worktop incl. wall-mounted brackets

Fittings supplied

Bracket for fronts and top board

Material

Aluminium frame

Warranty

2 years Warranty

This product is covered by a 2-year warranty against manufacturing defects.

