

Draft specification



**MANULIFT 6380LA - 60,0 cm**  
**Manufacturer:** Granberg

Article Info

**MANULIFT 6380L** is a manually adjustable worktop unit. Under the worktop, space is left for the knees and legs. Installations under the worktop, (brackets, water, sewers), can be concealed by telescopic cover panels which gives the kitchen a neat look. The height is adjustable by 300 mm at 25 mm intervals.  
A built-in gas spring facilitates the adjustment. The lift is prepared in the factory to facilitate easy installation.

| Art.no     | Description               | EAN           |
|------------|---------------------------|---------------|
| 6380LA-060 | MANULIFT 6380LA - 60,0 cm | 7340193103991 |

# Specifications

## Installation

Wall-mounted

## Front height

40 mm

## Height adjustment

Manually adjustable by 300 mm in intervals of 25 mm (700-1000 mm excl. top board)

A built-in gas spring facilitates height adjustment:

Pull out the locking pin, adjust the height with the help of the gas spring.

Lock the position with the locking pin.

## Max load

100 kg

## Frame depth

560-590 mm from wall

## Dimensions cover plates

2 pcs, width = width of the lift -10 mm, height 438 mm, thickness 12-20 mm

## Width worktop

Width = width of the lift

## Depth worktop

565-630 mm (15 mm shallower than worktops on fixed cabinets)

## Space to wall / adjoining cabinet

5 mm

## Space to wall (for tiles)

15 mm

## Tiling

From 700 mm above floor (alternatively all the way down to the floor)

## Delivery modules

Ready-mounted worktop incl. wall-mounted brackets

## Fittings supplied

Bracket for fronts and top board

## Material

Aluminium frame

## Warranty

2 years Warranty

This product is covered by a 2-year warranty against manufacturing defects.

